

# BULLET SUCTION EPDM Suction Hose



BulletSuction by Asoe is a EPDM suction hose manufactured with PE helix reinforcement, and the highest quality EPDM compounds. The rigid manufacturing standards of BulletSuction hose provide for extreme durability, flexibility, and chemical resistance compared to other suction hoses. Due to the high quality EPDM and PE materials used to manufacture BulletSuction hose it performs strong in cold environments. Factory testing showed BulletSuction remained flexible, without cracking or breaking, in temperatures dropping to as low as -40 °F.

## Technical Specifications

Part Number	Nominal Diameter (inches)	Inner Diameter (inches)*	Outer Diameter (inches)**	Working Pressure 20°C (PSI)	Vacuum Rating 20°C (Hg)	Unit Weight (lbs/ft)
BSH150	1.5	1.5	2.133	100	Full	.40
BSH175	1.75	1.77	2.165	100	Full	.47
BSH200	2.0	2.0	2.42	100	Full	.54
BSH250	2.5	2.56	3.0	100	Full	.69
BSH300	3.0	3.0	3.42	80	Full	.87
BSH400	4.0	4.0	4.54	65	Full	1.48
BSH600	6.0	6.0	6.65	50	28.0	1.63

\* Peak ribbing is additional .06-inches

\*\*Peak ribbing is additional .08-inches

Contact CPM Pipelines for higher temperature applications.

Standard length is 100-ft for all sizes. Available in 20-ft length for 6-inch.

## Features

- EPDM compounds are UV, ozone, abrasion and weather resistant
- Exceptional flexibility
- Rigid polyethylene helix
- Resistant to outdoor conditions

## Applications

- Vacuum pump dewatering
- Liquid frack removal
- Marine bilge discharge
- Liquid fertilizers
- Irrigation



3625 East Atlanta Avenue, Unit 2 ■ Phoenix, AZ 85040 ■ 602.904.9281

[cpmpipelines.com](http://cpmpipelines.com)